

# **Constant Temperature Water Bath LCTW-A12**



## Constant Temperature Water Bath LCTW-A12

Constant Temperature Water Bath LCTW-A12 is 9.9 L microprocessor controlled water bath. Equipped with a double row and four holes the temperature controller maintains temperature accuracy within  $\pm 0.5^{\circ}\text{C}$ . Exceeding temperature tracking alarm provides reliable sample protection. Safety features include a low liquid level switch, temperature limit warning and a high temperature cut-of.

### Features

- Microprocessor controlled temperature
- Double row four holes
- Over temperature tracking alarm
- Beaker hole size ( Customizable )

### Application

Used for incubation, boiling, inactivation, wet ashing, enzyme analysis, and a variety of clinical and industrial uses

### Specifications

Model No	LCTW-A12
Temperature range	RT + 5 $^{\circ}\text{C}$ ~ 100 $^{\circ}\text{C}$
Chamber capacity	9.9 L
Structure	Double row ; Four holes
Inner dimension ( W x D x H )	300 x 300 x 110 mm
Temperature accuracy	$\pm 0.5^{\circ}\text{C}$
Temperature resolution	0.1 $^{\circ}\text{C}$
Input power	1000 W
Time range	1 ~ 9999 min
Voltage	AC 220 V ; 50 Hz